



\*THESE CARE PRODUCTS ARE STOCKED BY HOMEWOOD SHOWROOMS

WOOD COATING – GRIP SEAL	
<b>Application process</b>	Ensure that the surface is completely free of oil, grease, stains and solvents. On new wood, sand until smooth. On previously varnished or oiled surfaces, remove by sanding or by using a paint stripper. Apply 3 thin even coats with 30 minutes between coats and 24 hours for the sealant to cure completely. <b>Can be Done DIY.</b>
<b>Sealing process</b>	A deep penetrating, UV resistant, non film forming, water based oil specially formulated to preserve, protect, nourish and enhance exterior wood surfaces. It contains UV protectors which protects the wood against the damaging effects of the sun, rain, heat and cold aswell as biocides which retard bacterial and fungal growth.
<b>Colour change to wood (on application)</b>	Darkens the wood - gives it a <b>WET</b> look. Saturates colours. Slightly lighter than oil - but darker than Rystix.
<b>Colour change to wood (long term)</b>	It <b>contains UV filters</b> so it protects the wood from rapid colour change in the long term. However woods with tannins (Teak & Oak) will still oxidise - it will slightly slow the process down. The coating itself does not age or change colour with time.
<b>Sheen and appearance on furniture</b>	If applied correctly is leaves a <b>Natural MATT</b> finish with the actual wood still seemingly in contact by touch.
<b>Suitable matrix use application</b>	Can be used up to an <b>X4 application</b> meaning it is the coating of <b>CHOICE</b> for <b>outdoor</b> use.
<b>Furniture cleaning</b>	Wipe down with warm soapy water or a damp cloth. <b>** AVOID AMMONIA or CAUSTIC PRODUCTS **</b>
<b>Maintenance Short Term</b>	Just keep surface clean.
<b>Maintenance Med &amp; Long Term</b>	Apply maintenance coat approx every 12 to 24 months or when wood appears to be faded. (Degree of exposure will determine how frequently a maintenance coat is required).
<b>Maintenance PROs</b>	<ul style="list-style-type: none"> <li>* Long lasting.</li> <li>* Very little maintenance required.</li> <li>* Seals and nourishes the wood.</li> <li>* Prevents ringing and other marking from hard use.</li> <li>* Has UV filters to protect the wood from the sun.</li> <li>* Easy to fix damage onsite - can be done DIY.</li> <li>* No peeling or colour change to the oil.</li> </ul>
<b>Maintenance CONS</b>	* Changes the wood colour on application.
<b>Fixing damage</b>	* Can easily be done <b>onsite and DIY</b> . Only damaged area needs to be sanded and oiled.
<b>Compatibility/Change NOTE : DIY Changes and use of inappropriate products MAY void our guarantee</b>	<p>This product is <b>ONLY</b> compatible with other Grip Seal products.</p> <p>Changing from Grip Seal to Danish Oil or Rystix is not easily done - full stripping and sanding of previous coating is necessary.</p>